

**PRH-M Series (10 - 30 W) Mini Radiant (PTC) Heaters**

| Model Number     | Part Number             | Voltage (VAC) | Heating performance (W)* | Frequency (Hz) | Power Consumption (W) | Starting Current (A) | Width in (mm) | Depth in (mm) | Height in (mm) | Weight lb (kg) |
|------------------|-------------------------|---------------|--------------------------|----------------|-----------------------|----------------------|---------------|---------------|----------------|----------------|
| <b>PRH 010-M</b> | 17000105317             | 110-250       | 10                       | 50/60          | 10                    | 1.0                  | 1.16 (29.5)   | 1.77 (45)     | 2.95 (75)      | .19 (.09)      |
| <b>PRH 020-M</b> | 17000205317             | 110-250       | 20                       | 50/60          | 20                    | 1.1                  | 1.16 (29.5)   | 1.77 (45)     | 2.95 (75)      | .26 (.12)      |
| <b>PRH 030-M</b> | 17000305317             | 110-250       | 30                       | 50/60          | 30                    | 1.2                  | 1.16 (29.5)   | 1.77 (45)     | 2.95 (75)      | .26 (12)       |
| <b>Design</b>    | Black anodized Aluminum |               |                          |                |                       |                      |               |               |                |                |

**FLH Series (10 - 150 W) Radiant Heaters - With extruded aluminum body**

|                 |             |         |     |       |     |     |           |           |            |            |
|-----------------|-------------|---------|-----|-------|-----|-----|-----------|-----------|------------|------------|
| <b>FLH 030W</b> | 17003005007 | 110-250 | 30  | 50/60 | 30  | 1.2 | 2.76 (70) | 1.97 (50) | 3.94 (100) | .55 (.25)  |
| <b>FLH 045W</b> | 17004505007 | 110-250 | 45  | 50/60 | 45  | 1.8 | 2.76 (70) | 1.97 (50) | 3.94 (100) | .55 (.25)  |
| <b>FLH 060W</b> | 17006005007 | 110-250 | 60  | 50/60 | 60  | 2.5 | 2.76 (70) | 1.97 (50) | 6.89 (175) | .99 (.45)  |
| <b>FLH 075W</b> | 17007505007 | 110-250 | 75  | 50/60 | 75  | 4.5 | 2.76 (70) | 1.97 (50) | 6.89 (175) | 1.12 (.51) |
| <b>FLH 100W</b> | 17010005007 | 110-250 | 100 | 50/60 | 100 | 5.0 | 2.76 (70) | 1.97 (50) | 6.89 (175) | 1.12 (.51) |
| <b>FLH 150W</b> | 17015005007 | 110-250 | 150 | 50/60 | 150 | 7.5 | 2.76 (70) | 1.97 (50) | 9.84 (250) | 1.7 (.77)  |

**FLH Series (250 - 400 W) Fan Heaters - With extruded aluminum body**

|                |                                     |     |     |       |     |     |           |            |              |             |
|----------------|-------------------------------------|-----|-----|-------|-----|-----|-----------|------------|--------------|-------------|
| <b>FLH 250</b> | 17025015007                         | 115 | 250 | 60    | 260 | 2.2 | 3.35 (85) | 4.09 (104) | 7.34 (186.5) | 2.29 (1.04) |
|                | 17025010007                         | 230 | 250 | 50/60 | 260 | 1.1 | 3.35 (85) | 4.09 (104) | 7.34 (186.5) | 2.29 (1.04) |
| <b>FLH 400</b> | 17040015007                         | 115 | 400 | 60    | 410 | 3.6 | 3.35 (85) | 4.09 (104) | 8.92 (226.5) | 2.65 (1.20) |
|                | 17040010007                         | 230 | 400 | 50/60 | 410 | 1.8 | 3.35 (85) | 4.09 (104) | 8.92 (226.5) | 2.65 (1.20) |
| <b>Design</b>  | Aluminum profile, brightly anodized |     |     |       |     |     |           |            |              |             |

\*Heating performance (Ta = +68 °F/+20 °C)  
Approvals (see the Quick Selection Chart found at the beginning of this section)



For additional technical data, drawings and manuals.  
[www.pfannenbergsusa.com](http://www.pfannenbergsusa.com)

**Available Models:**

**PRH-M**  
Ultra Compact Design  
(Integrated Cord)



**FLH**  
Compact & Large Designs  
(Quick Connects)

