

Pushbutton Enclosures for 22.5 mm Pushbuttons

Application -

Designed to offer protection for miniature oil-tight pushbuttons, switches, and pilot lights from dust, water, dirt and oil. For installation information, consult our Installation Manual at www.saginawcontrol.com.

Construction -

- 0.063" carbon steel.
- Continuously welded seams.
- Captivated cover screws thread into sealed wells.
- 4-way miniature pushbutton holes accept all brands of oil-tight pushbuttons, switches and pilot lights. Hole diameter is 0.87" (22.5 mm).
- Immediate removal of cover is permitted.
- Oil-resistant gasket.
- Welded mounting provision top and bottom of back.

Finish -

ANSI-61 gray powder coated inside and out.


IS2 - Industry Standards -

NEMA Type 4, 12 & Type 13
UL Listed Type 4 & 12
CSA Type 4 & 12
IEC 60529 IP66




PUSHBUTTON ENCLOSURES FOR 22.5 mm PUSHBUTTONS


| ENCLOSURE PRODUCT CODE A1 | | | | | |
|---------------------------|------------|-----------|-----------|-------------------|------------|
| Catalog No. | Height (A) | Width (B) | Depth (C) | Industry Standard | List Price |
| SCE-1PBGX | 3.25 | 3.25 | 3.50 | IS2 | 50.17 |
| SCE-2PBGX | 5.13 | 3.25 | 3.50 | IS2 | 55.18 |
| SCE-3PBGX | 7.00 | 3.25 | 3.50 | IS2 | 61.45 |
| SCE-4PBGX | 8.88 | 3.25 | 3.50 | IS2 | 67.71 |
| SCE-6PBGX | 8.50 | 6.00 | 4.25 | IS2 | 86.52 |
| SCE-9PBGX | 8.50 | 6.50 | 4.25 | IS2 | 95.31 |
| SCE-12PBGX | 10.38 | 6.25 | 4.25 | IS2 | 106.60 |



SCE-1PBGX




SCE-2PBGX




SCE-3PBGX




SCE-4PBGX



SCE-6PBGX



SCE-9PBGX



SCE-12PBGX

Phone (989) 799-6871
Fax (989) 799-4524



